

# FLIR FC-SERIES ID

Thermal Analytics Camera



FC-Series ID

The new FC-Series ID combines best-in-class thermal image detail and high-performance edge perimeter analytics in a single device that delivers optimal intrusion detection in challenging environments and extreme conditions. FC-Series ID cameras feature on-board video analytics optimized for FLIR's thermal sensors. Easy to set up and capable of classifying human or vehicular intrusions, FC-Series ID cameras provide reliable detection with very few false alarms, all without human intervention.

## RELIABLE ONBOARD ANALYTICS

*Accurately classify humans and vehicles*

- Auto calibration for depth setup for a simple and reliable configuration. No additional measurement tools are needed, requiring only a single installer on site
- Allows analytics in corridor mode, reducing the number of cameras and improving the total cost of ownership
- Target hand-off to PTZ camera auto-tracking

## INDUSTRY-LEADING IMAGE QUALITY

*Crisp, Clean Imagery for Unmatched Video Analytics Performance & Reliability*

- Superior image quality in low-contrast conditions
- FLIR's custom AGCs provide images with extremely high contrast
- Dynamic Detail Enhancement (DDE) creates sharp edges and contrast that improve analytics performance

## EXPANDED SELECTION OF HIGH-PERFORMANCE LENSES

*Wide Range of Lenses for Optimal Detection Ranges in All Conditions*

- Choose from 17 high performance lenses suitable for any perimeter or open area, including QVGA from 4° to 69° fields of view and VGA from 8° to 90° fields of view
- High performance optics deliver clear thermal video
- High analytic ranges to reduce number of cameras and total cost of ownership (TCO)



Create custom trip lines and regions of interest that will only set off alarms for human or vehicular intruders.

# Specifications

Thermal Camera Specs						
Model	FC-3XX ID			FC-6XX ID		
Array Format	320 x 240			640 x 480		
Detector Type	Long-Life, Uncooled VOx Microbolometer					
Spectral Range	7.5 µm to 13.5 µm					
Effective Resolution	76800			307200		
Pixel Pitch	Effective 34 µm (FC-344,332& 369) 17 µm (all other models)			17 µm		
Thermal Frame Rate	NTSC: 30 Hz - PAL: 25 Hz / 8.3 Hz					
Optical Characteristics	Model	FOV	F#, Focal Length	Model	FOV	F#, Focal Length
	FC-369 ID	69° × 56°	f/1.4, 9 mm	FC-690 ID	90° × 69°	f/1.2, 7.5 mm
	FC-344 ID	44° × 36°	f/1.0, 13 mm	FC-669 ID	69° × 56°	f/1.4, 9 mm
	FC-332 ID	32° × 26°	f/1.0, 19 mm	FC-644 ID	44° × 36°	f/1.0, 13 mm
	FC-324 ID	24° × 18°	f/1.0, 13 mm	FC-632 ID	32° × 26°	f/1.0, 19 mm
	FC-317 ID	17° × 13°	f/1.0, 19 mm	FC-625 ID	25° × 20°	f/1.1, 25 mm
	FC-313 ID	13° × 10°	f/1.1, 25 mm	FC-617 ID	17° × 14°	f/1.1, 35 mm
	FC-309 ID	9.2° × 7.0°	f/1.1, 35 mm	FC-610 ID	10° × 8.2°	f/1.25, 60 mm
	FC-305 ID	5.4° × 4.1°	f/1.25, 60 mm	FC-608 ID	8.6° × 6.6°	f/1.1, 75 mm
	FC-304 ID	4.3° × 3.3°	f/1.1, 75 mm			
E-Zoom	4x continuous E-Zoom					
Focus	Athermalized, focus-free					
Sensitivity	<35mK for F# 1.0 optics					
Video						
Composite Video NTSC or PAL	Hybrid system with IP & analog video, Dynamic NTSC or PAL settings					
Analog Video Output Composite	1Vp-p (PAL or NTSC), 1 x BNC 75Ω					
Video Compression	Two independent channels of H.264 (Restricted VBR and CBR, 10kbps-4Mbps, MPEG4, and MJPEG)					
Streaming Resolution	D1: 720x576, 4CIF: 704x576, Native: 640x512, Q-Native: 320x256, CIF: 352x288, QCIF: 176x144					
Thermal AGC Modes Features	Brightness, Contrast, Sharpness, Grey Shade Compression, Gamma, Smart Screen Balance					
Thermal AGC Region of Interest (ROI)	Default, Presets and User definable to insure optimal image quality on subjects of interest					
Analytics Management	Web-based configuration and management. Masking of analytic detection areas, adjustable sensitivity, automatic responses, remote I/O control					
Analytics Features	Region Entrance/Intrusion Detection, Crossover/Fence Trespassing; Auto/Manual Depth Setup, Human and Vehicle Rules, Hand-off target to PTZ racking, Tampering					
Image Uniformity Optimization	Automatic Flat Field Correction (FFC); Thermal and Temporal Triggers					
SD Card Snapshot Capture	Support for 32GB SD Card (sold separately)					
System Integration						
Ethernet	10/100 Mbps					
External Analytics Compatible	Yes					
Control Input/Output	1x Dry Contact in; 1x Relay Out (rated load 0.025A@ 5VDC)					
Network APIs	FLIR SDK, FLIR CGI, ONVIF Profile S					
Network						
Supported Protocols	IPv4, HTTP, Bonjour, UPnP, DNS, NTP, RTCP, TCP, UDP, ICMP, IGMP, DHCP, ARP, FTP, RTP/RTSP, Unicast/Multicast, TCP/IP, HTTP, IEEE 802.1X					
General						
Weight	Without sunshield: Lens Weight	7.5/9/13/19/25/35mm 1.8kg (4 lb.)	60mm 2.0kg (4.5 lb.)	75mm 2.2kg (4.75 lb.)		
	With sunshield: Lens Weight	7.5/ 9/ 13/ 19/ 25/ 35mm 2.2kg (4.75 lb.)	60mm 2.4kg (5.25 lb.)	75mm 2.5kg (5.5 lb.)		
Dimensions (L, W, H)	Without sunshield: 259 x 114 x 106 mm/10.2" x 4.5" x 4.2" With sunshield: 282 x 129 x 115 mm/11.1" x 5.1" x 4.5"					
Input Voltage						
Power Consumption	Source	POE (802.3af)	POE+ (802.3at)	12VDC	24VDC	24VAC(VA)
	Heater off	<5.5W	<5.5W	<5.5W	<5.5W	<8W
	Heater on (@ 100%)	N/A	<25W	<25W	<25W	<32W
Surge Immunity on AC Power Lines	CE: EN55032 Class A; FCC 47 CFR Part 15, Subpart B, Class A (within CISPR 22:2008 Class A limits)					
Surge Immunity on Signal Lines	EN 55024: 2010 and 55032: 2010 to 4.0kV on AC aux power lines; EN 50130-4:2011; IEC 62599-2:2010					

Environmental	
IP Rating (Dust & Water Ingress)	IP66 & IP67
Operating Temperature Range	-50°C to 70°C/-58°F to 158°F (Continuous Operation) -40°C to 70°C/-40°F to 158°F (Cold Start)
Storage Temperature Range	-50°C to 85°C/-58°F to 185°F
Humidity	0-95% relative humidity
Shock	MIL-STD-810G "Transportation"
Vibe	IEC 60068-2-27
De-Icing / Anti-Icing	MIL-STD-810 F, Method 521.2 - 6mm ice, 120 minutes with POE+, 4mm ice with POE af FC-304, FC-305, FC-610 & FC-608 with Cold Weather kit - not yet available.
Warranty & Regulatory	
Approvals	CE: EN55032 Class A; FCC 47 CFR Part 15, Subpart B, Class A (within CISPR 22:2008 Class A limits)
Certifications	IEC 60068-2-1:2007; IEC 60068-2-2:2007; ISTA-1A (Handling)
Compliance	RoHS Directive 2011/65/EU; WEEE 2012/19/EU
Warranty	Camera: 3 Years Sensor: 10 Years

**CORPORATE HEADQUARTERS**  
FLIR Systems, Inc.  
27700 SW Parkway Ave.  
Wilsonville, OR 97070  
USA  
PH: +1 866.344.4674

**EUROPE**  
FLIR Systems  
Luxemburgstraat 2  
2321 Meer  
Belgium  
PH: +32 (0) 3665 5100

FLIR Systems, Inc.  
6769 Hollister Ave,  
Goleta, CA 93117  
USA  
PH: +1 866.344.4674

**CANADA**  
FLIR Systems - Canada  
250 Royal Crest Court  
Markham, Ontario,  
Canada L3R 3S1  
PH: +1 866.344.4674

www.flir.com  
NASDAQ: FLIR

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2017 FLIR Systems, Inc. All rights reserved. Rev.12/11/17 [17-2965-SEC-PRO]