



# SMT-2212



## Key Features

- 22" FHD Monitor, support up to 1920\*1080 60Hz (FHD)
- Brightness 250 cd/m<sup>2</sup> (Typ) , Contrast 2000:1(Min), 3000:1(Typ)
- Viewing Angle (H/V) : 178°/178°, Response Time : 6.5ms(Typical)
- Video Input : HDMI(1), VGA(1)
- Frameless design with monitor stand
- Panel Life : 30,000 hours

# SMT-2212



## Specifications

### Display

Type	LED Monitor
Screen Size	21.45"
Max. Resolution	1920*1080 60Hz (FHD)
Brightness	250 cd/m <sup>2</sup> (Typ)
Contrast Ratio	2000 : 1(min) 3000:1 (Typical)
Aspect Ratio	16:9
Viewing Angle (H/V)	178°/178°
Display Color	1.07B Colors(Typ)
Response Time	6.5ms (Typical)
Panel Life	30,000 hours

### Interface

Video	Connectors	VGA (1), HDMI (1)
VGA	Connector	VGA
	Available Format	640 × 480@60Hz/72Hz/75Hz;800 × 600@60Hz/72Hz/75Hz;1024 × 768@60Hz/75Hz;1280 × 1024@60Hz/75Hz;1440 × 900@60Hz;1680 × 1050@60Hz ; 1920 × 1080@60Hz
HDMI	Connector	HDMI
	Available Format	640 × 480@60Hz/72Hz/75Hz;800 × 600@60Hz/72Hz/75Hz;1024 × 768@60Hz/75Hz;1280 × 1024@60Hz/75Hz;1440 × 900@60Hz;1680 × 1050@60Hz ; 1920 × 1080@60Hz

### On Screen Display

Functions	VESA™ DPM Compatible
Language	12 (English, French, German, Italian, Simplified Chinese, Traditional Chinese, Korean, Japanese, Espanola, Portuguese, Russian, Arabic )

### General

Electrical	Input Voltage	DC 12V 5A, Adapter included
	Power Consumption	<30W
Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)
Mechanical	Dimensions with Stand (WxHxD)	491.9*186.7*371.4*mm
	Dimensions without Stand (WxHxD)	491.9*36.1*289.4mm
	Weight	2.59 Kg
	Cabinet Color	Black
	VESA Mounts Interface	100*100mm

# SMT-2212



CAD

Unit: mm [inch]

## SMT-2212

