



SMT-3240

32" LED monitor



Key Features

- 32 inch UHD Monitor, support up to 3840×2160@60Hz
- Brightness 300 cd/m² (Typ) , Contrast 700:1 (Min) 1000:1 (Typ)
- Viewing Angle (H/V) : 178°/178°, Response Time : 14ms(Typical)
- Video Input : HDMI, DP
- Frameless design with monitor stand
- Panel Life : 30,000 hours
- Designed and tested on 24/7 operation

SMT-3240

32" LED monitor



Specifications

| | |
|---------------------|-----------------------------|
| Display | |
| Type | LED Monitor |
| Screen Size | 31.5" |
| Max. Resolution | 3840*2160 60Hz (UHD) |
| Brightness | 300 cd/m ² (Typ) |
| Contrast Ratio | 700:1 (Min) '1000:1 (Typ) |
| Aspect Ratio | 16:9 |
| Viewing Angle (H/V) | 178°/178° |
| Display Color | 1.07B Colors(Typ) |
| Response Time | 14ms(Typical) |
| Panel Life | 30,000 hours |

| | | |
|-----------|------------------|--|
| Interface | | |
| Video | Connectors | HDMI 2.0(1), DP1.2(1) |
| | Connector | HDMI |
| HDMI | Available Format | 640 x 480@60Hz,800 x 600@56Hz/60Hz,1024 x768@60Hz,1280 x 720@60Hz,1280x800@60Hz,1280x960@60Hz,1280x1024@60Hz, 1360x 768@60Hz,1440x900@60Hz,1680x1050@60Hz,1920x1080@60Hz,2560 x 1440@60Hz,3840 x 2160@60Hz,640 x 480P@60Hz,720x480P60Hz,1280 x 720P@60Hz,720x576P@50Hz , 1280x720P@50Hz,1920x 1080I@50/60Hz,1920x1080P@50/60Hz,720x480P@60Hz,3840x 2160P@30/50/60Hz,1440x480P@60Hz,1440x576P@50Hz,1440x 576P@50Hz,1440x480P@60Hz |
| | Connector | DP |
| DP | Available Format | 640 x 480@60Hz,800 x 600@56Hz/60Hz,1024 x768@60Hz,1280 x 720@60Hz,1280x800@60Hz,1280x960@60Hz,1280x1024@60Hz, 1360x 768@60Hz,1440x900@60Hz,1680x1050@60Hz,1920x1080@60Hz,2560 x 1440@60Hz,3840 x 2160@60Hz,640 x 480P@60Hz,720x480P60Hz,1280 x 720P@60Hz,720x576P@50Hz , 1280x720P@50Hz,1920x 1080I@50/60Hz,1920x1080P@50/60Hz,720x480P@60Hz,3840x 2160P@30/50/60Hz,1440x480P@60Hz,1440x576P@50Hz,1440x 576P@50Hz,1440x480P@60Hz |
| | Connector | Audio Out |
| Audio | Connector | Audio Out |
| | Output Signal | Loop-through line level(PC only), Speakers : 6Ω 2W x 2 |

| | |
|-------------------|--|
| On Screen Display | |
| Functions | VESA™ DPM Compatible |
| Language | Korean, English, Русский, Deutsch, Français, Español, Italiano, Português, Chinese (Simplified), Chinese (Traditional), Japanese, Arabic |

| | | |
|---------------|-----------------------|----------------------------|
| General | | |
| Electrical | Input Voltage | AC 100 ~ 240V(50/60Hz) |
| | Power Consumption | <55W |
| Environmental | Operating Temperature | 0 ~ +40°C (+32°F ~ +104°F) |
| | Operating Humidity | 10% ~ 80% (non-condensing) |

| | | |
|------------|----------------------------------|---|
| Mechanical | Dimensions with Stand (WxHxD) | 714.6*485.7*200.9mm |
| | Dimensions without Stand (WxHxD) | 714.6*445.6*53.7mm |
| | Weight | 8.0kg(with stand), 6.5Kg(without stand) |
| | Cabinet Color | Black |
| | VESA Mounts Interface | 100*100mm |