

Overdoor Light

Part No. **NC806C**



Overview

- Provides visual indication of 800 Series Alarm calls outside bedrooms, WCs and any other area fitted with an 800 Series calling device.
- Indicates Standard calls via a constant red light and Emergency calls via a pulsing red light.
- Dual red LEDs and triangular diffuser make it highly visible from a distance.
- Mounts on a standard UK 25mm single gang flush or surface back box.
- Can also used as an 'area indicator' at corridor junctions, staff workstations, etc.
- Finished in tough, durable ABS plastic.
- Also available as part of the NC951 Accessible Toilet Alarm kit.
- Overdoor Lights c/w Sounders and Stainless steel version also available.



More Information

Technical Specifications

Quiescent current	0mA (none).
Alarm current	Determined by the type of control equipment and number / type of field devices connected to the system.
Indicators	Dual ultra-bright red Alarm LEDs (lit constantly for standard calls, intermittently for emergency calls).
Controls	None (the device is controlled by the system calling device it is connected to).
Connections	1 (Signal); -Ve (Negative); +Ve (Positive).
Onboard Sounder	No,



Onboard Infrared Receiver No.
Product dimensions (mm) 87 W x 87 H x 68 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish Translucent plastic.
IP Rating IP41.
Weight 50g.
Operating conditions/temperature -5°C to +40°C. Max. relative humidity 95% non-condensing.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom