

SPI-50 IR Illuminator




Key Features


- Compatible IR Illuminator for TNU-6320
- Wavelength: 850nm
- Angle : 25°

Dimensions



	 _
	e





	SPI-50	
OPERATIONAL		
LED Type	IR LED	
Distance Performance	200m (656.17ft)	
Number of LED	9ea	
Angle	25°	
Wavelength	850nm	
Control	Via remote control : day&night, photocell sensitivity	
COMMUNICATION		
Between Camera & Illuminator	RS-485 9600bps	
Illuminator Identification	Fixed address 1	
EXTERIOR		
Dimensions (WxHxD)	112.0x 153.2 x 65.2mm (4.41" x 6.03" x 2.57")	
Weight	0.9kg (1.98 lb): 1ea	
Material	Aluminum + PC Cover	
ELECTRICAL		
Power	24V AC (±10%)	
Power Consumption	Max.light : 24W	
ENVIRONMENTAL		
Operational Temperature	$-40^{\circ}C \sim +60^{\circ}C (-40^{\circ}F \sim 140^{\circ}F)$	
Certification	EMC (FCC, CE, VCCI, RCM, KC)	
Ingress Protection	IP67	

* The lastest product information / specification can be found at hanwha-security.com
* Design and specifications are subject to change without notice.
* Wisenet is the proprietary brand of Hanwha Techwin, formerly known as Samsung Techwin.







