SUMMARY





High resilience video architecture via direct-to-storage from IP cameras

The unique TRINITY™ system architecture eliminates NVR servers, using IP cameras recording direct to Veracity's COLDSTORE™ sequential recording system.

- Serverless system direct-to-storage from IP camera
- High-performance mega-pixel camera recording
- Simplified system architecture design for very high reliability
- Camera-level failover feature
- Ideal for unmonitored or remote access systems
- Very long archive periods possible for megapixel cameras
- Easy integration with PSIM systems



TECHNICAL SPECIFICATION

SYSTEM	TRINITY® (Veracity Direct-To-Storage System Architecture) Three component system: COLDSTREAM™ IP camera code. COLDSTORE™ storage system. VIEWPOINT™ client player application (or third-party system).
PLATFORM	TRINITY-capable IP Cameras . Typically those which can support on-board thirdparty applications such as video analytics and similar. Currently supported : Axis Communications (ACAP), Samsung Techwin (WiseNetIII), UDP Technology, In development : Vivotek (VDAP), HIK Vision (HEOP)[see Veracity website for latestinformation]+ COLDSTORE + Client PC.
OPERATING SYSTEM	IP Camera As per IP Camera (typically Linux). COLDSTORE Linux. COLDSTREAM Windows 7 or higher (or as per third party application).
SYSTEM TYPE	Serverless direct to storage system with COLDSTORE as storage target.
CLIENT	VIEWPOINT Player application or third party application incorporating the Media SDK (available upon request). Currently supported by: i-Comply, VMS UK, Hawha Techwin [see Veracity website for latest information].
INSTALLATION & CONFIGURATION	IP Camera COLDSTREAM code installed via Veracity Camera Manager. COLDSTORE TRINITY channel keys installed via COLDSTORE Manager. Client Windows installer or as per third-party client requirements.
RECORDING	Multiple recording modes including standard, automatic failover, redundant, camera internal (second-level failover). Automatic re-sync to COLDSTORE after network loss with internal second level failover. Image resolution, quality, frame rate and compression type as defined by IP camera and configuration.
CAMERA CHANNELS	Up to 96 x HD channels per COLDSTORE (including Compact). Any number of camera channel keys may be purchased at any time, allowing easy upgrade.
LIVE VIEW	Via VIEWPOINT client player application. Third-party applications may provide live view via the Media SDK or by live view direct from supported cameras.
PLAYBACK	Play, pause, stop, fast-forward, rewind, play next or previous file from multiple channels and multiple COLDSTOREs. VIEWPOINT incorporates easy to use time-bar system. Post-recording Pan-Tilt-Zoom supported, including 360 view de-warping.

TECHNICAL SPECIFICATION

TRINITY

EXPORT

VIEWPOINT: Easy export of video clips (including audio & meta-data) for evidence purposes. Multiple exports tasks may be set up and run concurrently. Entire disk volumes may be extracted from COLDSTORE if required for instant evidential seizure of large data volumes and replayed via the Veracity DISKPLAY - supported by VIEWPOINT and Media SDK.

SYSTEM MONITORING

 $\mbox{VIEWSTORE} \mbox{$^{\top}$M} : \mbox{Automatic visual display systems for COLDSTORE status} \\ \mbox{monitoring (see separate data sheet)}.$

SCALABILITY

The TRINITY system has been developed for simple scaling to large numbers of cameras. The serverless architecture enables the simple creation of large, very high capacity, systems systems with robust failover.

SYSTEM FEATURES

Direct to storage from supported IP cameras.

Camera-level failover system. Redundant recording option.

Network loss failover (to camera internal storage). Automatic "catch-up" after network interruption. Robust and simple system architecture.

Simple scalability to large camera counts and high capacity. Choice of Client Application – may be changed at any time.

PART CODES

CSTREAM-KEY

VW-POINT-SW

VW-STORE-SYS

CSTORE15-3U-DU-UK
CSTORE15-3U-DU-EU

CSTORE15-3U-DU-US

CSTORE8-C-EU

CSTORE8-C-EU

CSTORE8-C-UK

COLDSTREAM Channel Licence

VIEWPOINT Client Player

VIEWSTORE Storage status monitor

COLDSTORE 15 bay 3U unit, PSU with cables for UK

COLDSTORE 15 bay 3U unit, PSU with cables for EU

COLDSTORE 15 bay 3U unit, PSU with cables for US

COLDSTORE Compact 8x2.5" compact storage array, & PSU, cables for UK

COLDSTORE Compact 8x2.5" compact storage array, & PSU, cables for EU

COLDSTORE Compact 8x2.5" compact storage array, & PSU, cables for US



Americas Sales

Veracity USA Inc. 17000 Preston Road Suite 120 Dallas TX 75248 USA Tel: 1-800-679-1590

Tel: 1-800-679-1590 Fax: 1-800-679-0714 www.veracityglobal.com sales@veracityusa.com

EMEA Sales

sales@veracityuk.com

Veracity UK Ltd
Prestwick International Aerospace Park
4 Dow Road
Prestwick
KA9 2TU
UK
Tel +44 (0) 1292 264967
Fax +44 (0) 845 528 1081
www.veracityglobal.com

© Veracity UK Ltd 2017 All rights reserved. WV2.5 UK Under no circumstances should this document be reproduced, distributed or changed, partially or wholly, without written, formal authorisation from Veracity UK Ltd.