

DS-1200KI Network Keyboard



- Full-featured network keyboard
- Supports various cameras, NVRs, DVRs
- Flexible 4-axis joystick
- Buttons can be used to perform powerful functions
- 128 × 64 screen displays all important information

▪ Specification

Interface	
USB Interface	1 × USB 2.0
Serial Interface	1 RS-232, 1 RS-422, 1 RS-485
Network Interface	1 × 10/100 Mbps self-adaptive Ethernet interface
General	
Working Temperature	-10 to +55° C (14 to 131° F)
Working Humidity	10% to 90%
Net Weight	≤ 1 kg (2.2 lb)
Dimensions (W × H × D)	435 mm × 110 mm × 193 mm (17.1 inch × 4.3 inch × 7.6 inch)
Power Consumption	≤ 4.5 W
Power Supply	12 VDC
Display	128 × 64 pixel screen
Joystick	4-axis joystick
Certification	
Obtained Certification	CE-EMC/CE-LVD/ROHS/CB/UL/FCC-SDoC/BIS

▪ Available Model

DS-1200KI

DS-1200KI(B)

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq