

DS-2CE16D0T-ITE(C) 2 MP PoC Fixed Mini Bullet Camera



- 2 MP PoC bullet camera
- 2.8 mm and 3.6 mm fixed focal lens
- Up to 20 m IR distance for bright night imaging
- Water and dust resistant (IP67)
- Transmits both HD video and power over the same coaxial cable




▪ Specification

Camera	
Image Sensor	2 MP CMOS
Signal System	PAL/NTSC
Resolution	1920 (H) × 1080 (V)
Frame Rate	PAL: 1080p @ 25 fps NTSC: 1080p @ 30 fps
Day & Night	ICR
Min. Illumination	0.01 Lux @(F2.0, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Lens	Fixed focal lens, 2.8 mm and 3.6 mm optional
Field of View	2.8 mm, horizontal FOV: 101°, vertical FOV: 56°, diagonal FOV: 118° 3.6 mm, horizontal FOV: 78°, vertical FOV: 42°, diagonal FOV: 92°
Lens Mount	M12
WDR (Wide Dynamic Range)	Digital WDR
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°
Image	
Day/Night Mode	Auto/Color/BW (Black and White)
Image Mode	STD/HIGH-SAT
AGC	Yes
White Balance	Auto/Manual
AE (Auto Exposure) Mode	DWDR, BLC, HLC, Global
Noise Reduction	2D DNR
Language	English
Function	Brightness, Smart IR, Sharpness
Interface	
Video Output	1 HD analog output
General	
Power	12 VDC ± 25%, 0.24 A, max. 2.9 W, PoC.af, *You are recommended to use one power adapter to supply the power for one camera.
IR Range	Up to 20 m
Operating Conditions	-40°C to 60°C (-40°F to 140°F). Humidity: 90% or less (non-condensing)
Protection Level	IP67
Material	Metal
Communication	HIKVISION-C
Dimension	∅70 mm × 158.6 mm (∅2.76" × 6.24")
Weight	Approx. 335 g (0.74 lb.)

▪ Available Model

DS-2CE16D0T-ITE (C)


▪ Dimension



Unit: mm (inch)

- Accessory
- Optional

**DS-1280ZJ-XS
Junction Box**



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

