

CODE: **S116** v.1.0/l
 TYPE: **S116 16-port switch for 16 IP cameras**

EN**



Features:

- 16 ports switch
- 16 PoE ports 10/100Mb/s (data and power supply)
- 2 ports 10/100/1000Mb/s (G1/G2 ports) (UpLink)
- **Long Range** mode (up to 250m)
- 30W for each PoE port, supports devices complaint with the IEEE802.3af/at (**PoE+**) standard
- Supports auto-learning and auto-aging of MAC addresses (16K size)
- LED indication
- Additional assembly elements
- warranty – 2 year from the production date

DESCRIPTION

S116 is a 16-ports PoE switch designed to supply IP cameras operating in IEEE 802.3af/at standard. Automatic detection of any devices powered in the PoE/PoE+ standard is enabled at the 1 – 16 ports of the switch. The G1 and G2 ports is used for connection of another network device via RJ45 connector. The LEDs at the front panel indicate the operation status.

The PoE technology ensures a network connection and reduces installation costs by eliminating the need to supply a separate power cable for each device. This method allows supplying other network devices, such as IP phone, wireless access point or router.

TECHNICAL PARAMETERS

Ports	16 x PoE (10/100Mb/s) (RJ-45) 2 x UpLink (10/100/1000Mb/s) (RJ-45) with connection speed auto-negotiation and MDI/MDIX Auto Cross)
PoE power supply	IEEE 802.3af/at (1+16 ports), 52 V DC / 30 W at each port *
Operating modes	Long Range, VLAN
Protocols, Standards	IEEE802.3, 802.3u, 802.3x CSMA/CD, TCP/IP
Bandwidth	14,8Gbps
Transmission method	Store-and-Forward
Optical indication of operation	Switch power supply; Link/Act; PoE Status
Power supply	~100-240 V; 50/60 Hz; 3,1-1,8 A
Operating conditions	temperature -10°C ÷ 40°C, relative humidity 5% - 90%, no condensation
Dimensions	W=270, H=44, D=181 [+/- 2mm]
Additional equipment	bracket for Rack 19"
Cable length AC	1,2m
Net/gross weight	1,7 / 1,9kg
Protection class EN 60950-1:2007	I (first)
Storage temperatur	-20°C ÷ 60°C
Declarations, warranty	CE, 2 year from the production date

* The given value of 30 W per port is the maximum value. The total power consumption should not exceed 160 W when all PoE ports are being used.

Connection schemes

