

# VVS302-PLUS

Seismic detector for ATM's and night deposit boxes, NC contact

## Superior detection

---

The VVS3xx-PLUS series seismic detectors are designed to detect attempts to break into vaults, safes, night deposit boxes, automatic teller machines (ATM's) and other reinforced physical areas such as data storage's and filing cabinets. These seismic detectors react to the characteristic vibration patterns of all breaking-and-entering tools, such as hammers, drills, diamond saws, hydraulic pressure tools and thermal tools like welding torch and thermal lance. They sense vibrations that occur within a 3 to 14 meter radius of where they are mounted, depending on the material and design of the protected object.

## Excellent false alarm immunity

---

At the same time the seismic detectors allow for normal human activity around the protected area without the risk of creating unwanted alarms. To achieve this high level of accuracy, each detector features "three detectors in one". All three channels (counting, integration, and explosion) analyze the signal frequencies, duration and amplitude, in order to differentiate between random environmental disturbances and real intruder attack. The end result is detectors with excellent detection and false alarm immunity.

## Testing & accessories

---

The VVS3xx-PLUS series provides two different test functions: automatic or manual activated. You can choose between an internal test of the detector electronics or, by using the test transmitter VVT705, do a functional test of the detector and its physical contact to the protected object. A complete range of accessories is provided for all kinds of applications to achieve the highest security.



## Details

---

- Detects all known types of attack
- Advanced signal processing differentiates between ambient noise and real attacks
- Protects any solid structure
- Remote test capability
- Adjustable sensitivity
- Advanced tamper protection
- Complete line of accessories
- Easy to install

# VVS302-PLUS

Seismic detector for ATM's and night deposit boxes, NC contact

## Technical Specifications

### General

Application Type	ATM, Night Safe Deposit Boxes
Tamper protection	Temperature 84°C, drill shield, opening contact, pry-off contact
Alarm indication	LED-indication screw no. 3
Low voltage alarm	7.5 V

### Detection

Range	3 to 14 m radius
Sensitivity adjustment	5 steps of approx. 6 dB each

### Inputs/outputs

Alarm contact	NC
Test output	Yes

### Electrical

Power supply value	9 to 15 VDC
Current consumption	8.6 mA

### Physical

Physical dimensions	81 x 101 x 28 mm
Net weight	380 g
Colour	Grey (RAL 7035)

### Environmental

Operating temperature	-20 to +55°C
Relative humidity	0 to 90% noncondensing
IP-rating	IP30

### Operating voltage

9 - 15 Vdc, 2 V max ripple ptp

### Current draw

Nominal 8.6 mA

### Alarm contact

NC

### Alarm indication

LED output (terminal 3)

### Sensitivity adjustment

5 steps of approx. 6 dB each

### Test output

Analog output (terminal 4)

### Range

3 - 14 m radius - depending on attack tool

### Tamper protection

Temperature	84 °C
Drill shield	Yes
Tamper contact	Yes
Pry-off tamper	Yes

### Low voltage alarm

7.5 Vdc

### IP rating

IP30

### Operating temperature

-20°C till +55°C

### Relative humidity

90% at 30°C

### Dimensions (L x W x H)

81 x 101 x 28 mm

### Color

Grey, RAL 7035

### Weight

380 g